

# ECOFOAM PLUS

HIGH PERFORMANCE ALKALINE LONG CLING FOAM DETERGENT

- For fat and protein removal on heavily soiled areas
- Long cling foam
- Remains fully effective regardless of water hardness



## RECOMMENDED USAGE



### Application

Use to spray the roof, walls and posts with a pressure washer set at a low pressure with a wide angled jet or via foam generating equipment.

Remove all gross soiling. Foam all surfaces with Ecofoam Plus. Wash down thoroughly with clean water.



### Dilution Rates

Apply via a foaming lance at a dilution rate of 1:100 for normal conditions or 1:50 for heavy soiling. Leave for 10 - 30 minutes dependent on the level of soiling then rinse off thoroughly with clean water.



### Composition

A formulation of chelating agents, surfactants and alkaline builders.



**Storage:** Store in a dry place away from acids

**Pack Size:** 4x5, 25, 200 & 1000 litre

**Shelf Life:** 2 years from date of manufacture



FOR HEALTH & SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET

KILCO (INTERNATIONAL) LTD.  
BROOMHOUSES 2 INDUSTRIAL ESTATE  
OLD GLASGOW ROAD, LOCKERBIE.  
DG11 2SD

Tel: +44 (0) 1576 205 480  
Fax: +44 (0) 1576 205 483  
Email: [enquiries@kilco.co.uk](mailto:enquiries@kilco.co.uk)