

# HEAVY DUTY CLEANER

HEAVY DUTY CLEANER FOR SURFACE AND IMMERSION CLEANING

- Heavy duty pre-wash detergent
- Highly effective against organic matter
- Foaming ability for surface cleaning



## RECOMMENDED USAGE



A highly caustic product containing chelating and sequestering agents and surfactants for immersion removal of heavy soil from movable equipment such as slats and filters

### APPLICATION

Remove all loose soiling where possible. Add Heavy Duty Cleaner to immersion bath and dilute with water. Immerse item for minimum of 8 hours or overnight.



For surface and equipment application, spray at low pressure or preferably foam Heavy Duty Cleaner ensuring all surfaces are well covered. Rinse thoroughly with clean water before application of any biocides.



### RECOMMENDED DILUTION RATES

For slat cleaning, standard recommended dilution is 40 litres per 3000 litres water (1:75). For heavy soiling use 1:50 dilution ( 60 litres per 3000 litres water).

**Storage:** Store in a dry place away from acids

**Pack Size:** 4x5, 25, 200 & 1000 litre

**Shelf Life:** 2 years from date of manufacture



FOR HEALTH & SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET

KILCO (INTERNATIONAL) LTD.  
BROOMHOUSES 2 INDUSTRIAL ESTATE  
OLD GLASGOW ROAD, LOCKERBIE.  
DG11 2SD

Tel: +44 (0) 1576 205 480  
Fax: +44 (0) 1576 205 483  
Email: [enquiries@kilco.co.uk](mailto:enquiries@kilco.co.uk)