

**ECOFOAM PLUS** 

Page: 1

**Revision date:** 01/04/2015

Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name: ECOFOAM PLUS

Product code: AF7886

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning of animal accomodation and associated equipment

# 1.3. Details of the supplier of the safety data sheet

Company name: Kilco (International) Ltd

Broomhouses 2 Industrial Estate

Old Glasgow Road

Lockerbie DG11 2SD

United Kingdom

Tel: +44 (0) 157 620 5480

Email: sds@kilco.co.uk

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 207 858 1228

## **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CHIP: C: R35

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe burns.

#### 2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

**ECOFOAM PLUS** 

Page: 2

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases: R35: Causes severe burns.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

S28: After contact with skin, wash immediately with plenty of water.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

# TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent	
200-573-9	64-02-8	Xn: R22; Xi: R41	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%	
SODIUM HYDROXIDE					
215-185-5	1310-73-2	C: R35	Skin Corr. 1A: H314	1-10%	
2-(2-BUTOXYETHOXY)ETHANOL					
203-961-6	112-34-5	Xi: R36	Eye Irrit. 2: H319	1-10%	
DODECANOL-1					
203-982-0	-	Xi: R36; N: R50	Eye Irrit. 2: H319; Aquatic Acute 1:	<1%	

H400

### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

**ECOFOAM PLUS** 

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid. Mark out the contaminated area with signs and

prevent access to unauthorised personnel.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

**ECOFOAM PLUS** 

Page: 4

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): The identified uses for this product are detailed in Section 1.2

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

## Hazardous ingredients:

# SODIUM HYDROXIDE

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

## 2-(2-BUTOXYETHOXY)ETHANOL

UK	67.5 mg/m3	101.2 mg/m3	-	-
----	------------	-------------	---	---

# **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable.

[cont...]

**ECOFOAM PLUS** 

Page: 5

**Relative density:** 1.090 – 1.110

**pH:** > 12.5

#### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

#### **SODIUM HYDROXIDE**

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

## 2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Corrosivity	OPT INH DRM	Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**ECOFOAM PLUS** 

Page: 6

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects:

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

#### **Section 14: Transport information**

### 14.1. UN number

UN number: UN1719

## 14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.

(SODIUM HYDROXIDE)

# 14.3. Transport hazard class(es)

Transport class: 8

# 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

**ECOFOAM PLUS** 

Page: 7

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

Tunnel code: E
Transport category: 3

#### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

R22: Harmful if swallowed.

R35: Causes severe burns.

R36: Irritating to eyes.

R41: Risk of serious damage to eyes.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product. Kilco

(International) Ltd, Registered Office: 1A Trench Road, Mallusk, Newtownabbey, Belfast

BT36 4TY. Place of Registration: Northern Ireland, Registration Number: NI3240